优质的售后服务 uality after-sales service

1小时服务回复 1 Hour service

接到电话,一小时内回复处理意见

We will reply to your service request call within one hour with solution suggestion

12小时处理 12 Hours service

12小时内解决方案

The GM's office will handle customer's complaints directly and reply within 12 hours with solution.

24个小时到位 Reach within 24 working hours

急技术问题,服务网点500公里内,维护人员24小时到位 The maintance team will be in place within 24 working hours for customers located within 500km of the service point range

1次/月 1 Time/month

每月一次客服回访,专心、专业只为让客户舒心、放心 By re-visiting the customers on a monthly basis ,customers can rest assured and worriless

售前服务 Pre-sale Service

在机器发货前,可安排人员到我司学习培训,我司有专业的电气工程师、机械工程师进行授课,同时还会安排技术工程师现场培训,在机器上面更换不同尺寸的新产品,培训的同时也对整台机器再次进行售前质检。

Before delivery, customer can arrange personnel to train in our company. We have teachers of professional electronic engineer and mechanical engineer and we will company arrange technologies in the machine arrange technologies.

售中服务 Sale Services

当客户收到设备后,我们会安排技术工程师进行安装调试,并免费提供培训服务,且再次进行大货生产的培训服务。 When the machine reached your company, we will arrange technical engineers to install and debug, and provide a week of training service for free of charge, then carry out the training services for the production in bia batch.

售后服务 After-sales Service

建立完善的客户档案,随时记录用户的使用状况,并定期回访查询设备使用状况和性能,以及提供产品的软硬件更新,功能改进等专业服务;资深强大的售后服务队伍、完备的备用件仓库,迅速、及时解决用户要求。 We will estalish completed customer files,record the customer usage at any time, and re-visit to find out usage status and performance of equipment regularly.And also provide professional services of software and hardware updates, functional improvements. We have senior and strong after-said

广东力顺源智能自动化有跟公司

Guangdong LiShunYuan Intelligent Automation Co.,Ltd

工厂地址:广东省东莞市道滘镇南丫工业区南阁东路 FACTORY ADD: NanGe EastRoad,Nan Ya Industrial Zone,Daojiao Town Dongguan,Guangdong,China

电话/TEL:+86-0769-88116769/23174550/400-056-7199

传真/FAX:+86-0769-8811 6772 / 2317 4590

网址/WEB: www.dglyjx.com



Contact Information:

WhatsApp&WeChat: 18814254225





LY-485C 视觉定位机

Visual positioning machine

生产速度快,多功能化

LY-485C



LY-485C 视觉定位机

Visual positioning machine

LY-485 系列产品,飞达送纸、过胶和输送带都采用独立的伺服驱动。采用YAMAHA机械手和摄像头成像定位,可实现天地盒、皮壳、抽屉盒、异型盒等产品的精准定位,适用于各种需要过胶定位的高档精品盒,如:手机盒、化妆品盒、珠宝首饰盒、手表盒、酒盒、烟盒等制作。

A series of LY-485 products, The parts of Feida feeding, gluing and conveyor belt use independent servo drive. The positioning part adopts YAMAHA robot arm, and camera to visually position the inner box, which can realize high accuracy in the rigid box, bookcase, drawer box, irregular shape boxes. It is suitable for a variety of high-quality gift box which need gluing, like phone box, cosmetic box, Jewelry box, watch box, wine box, cigarette box, etc.

产品特性 Product Features

■ 采用两个进口500万像素工业相机、YAMAHA机械手定位,精度±0.1mm.

Using two industrial cameras with five mega pixels, and YAMAHA robot arm to position, high positioning accura cy(±0.1mm).

■ 生 产 速 度 快 , 天 地 盒 25-35pcs/min;皮壳及对20-30 pcs/min.

High production rate, rigid box production speed up to 25-35pcs/min; case maker and mounted product speed up to 20-30pcs/min. ■ 采用独立的人机控制系统, 词机时间 短、转版快。

Using an independent man-machine control system, transfer machine time is short, fast transfer version.

■ 送纸稳定,不易吸双张,降低产品废品率

Feeding stably , does not suck up double sheets easily, reduce product rejection rate. ■ 独立过胶定位模块,可拾配贴用机、拼放机、气动成机、皮壳机等生产皮壳、对裱、天地盖及开天窗产品,对未来产品可延伸性强。

ndependent gluing & positioning module, can be optionally matched with corner pasting machine, splicing board box making machine, pneumatic machine and case maker machine etc to produce of case maker, mounted, rigid box and opening window. It is strong and extensible for the future products

主要技术参数 Technical Parameters

面纸尺寸(L*W)	Paper size (L*W)	L 180-850mm
		W 95-600mm
成品(纸盒)尺寸(L*W*H) Finished box size (L*W*H)		L 45-600mm
		W 45-400mm
		H 10-120mm
		L 100-800mm
皮壳成品尺寸	Case maker finished box size (L*W)	W 80-400mm
面纸厚度	Paper thickness	80-300g/m²
面纸最大放置高度	Max. paper stacking height	400mm
纸板厚度	Cardboard thickness	1-3mm
生产速度	Production rate	25-35pcs/min
定位精度	Positioning accuracy	±0.1mm
需求气压	Air pressure	0.6-0.8MPa
胶桶容量	Glue tank capability	50KG
电源	Power supply	380V/50Hz/3phases
额定功率	Constant power	18KW
机器重量	Machine weight	1500KG
整机尺寸	Machine dimension	定皮壳 L7500×W2400×H2000mm
		定天地盒 L7500×W1500×H2000mm
		定天地盒 L7500×W1500×H2000mm